



Item	Qty	Designation	Specification	Net Weight
7	8	NUT	M6M M5 FE/Z-NI Black	
6	8	WASHER	RB M5 ISO 7089 Z-Ni Black	
5	8	SCREW	M6SF-TT M5x20 NYSEAL Z-NI Black	
4	1	INSTALLATION INSTR.		
3	1	ASSEMBLY GEL	-	
2	4	CM 40/10-32	0+9,5-32,5	
1	1	COMSEAL 16 FRAME	POWDERCOATED ALUMINUM	

ROXTEC INTERNATIONAL AB BOX 540 S-371 23 Karlskrona TEL: +46 455 366700 FAX: +46 455 82012	Designed by se-jenboh	Date 2008-03-05	General tolerance EN ISO 2768-1/2-m/K EN ISO 13920-BF	Welded details EN ISO 5817-B EN ISO 10042-B	General surface roughness, Ra 12,5	Total Weight
	Checked by se-jorake	Format	Title COMSEAL 16/4 ASSEMBLY KIT	Projection method 		Rev C
Approved by se-jorake			Scale	Drawing number S1013361		
Restricted due to Information Drawing						

We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©ROXTEC INTERNATIONAL AB

Rev	Type of revision	Date	Sign
C	CHANGE TO INSTALLATION INSTRUCTION	2012-03-22	se-henols