



8	6	NUT	M6M M5 FE/Z-NI Black
7	6	WASHER	RB M5 ISO 7089 Z-Ni Black
6	6	SCREW	M6SF-TT M5X20 NYSEAL Z-Ni Bl
5	1	INSTALLATION INSTR.	
4	1	ASSEMBLY GEL	-
3	1	CM 20w40	0+3.5-16.5
2	2	CM 40 10-32	0+9.5-32.5
1	1	COMSEAL 10 FRAME	POWDER COATED ALUMINUM

Item	Qty	Designation	Specification	Net Weight
ROXTEC INTERNATIONAL AB BOX 540 S-371 23 Karlskrona TEL: +46 455 366700 FAX: +46 455 82012		Designed by se-jenboh	Created Date 2008-03-05	General tolerance ISO 2768-1/2-m/K EN ISO 13920-BF
		Approved by se-jorake	Approved Date 2012-04-04	Welded details EN ISO 5817-B EN ISO 10042-B
		Format A3	Scale 1:1	General surface roughness, Ra 12,5 -
		Title COMSEAL 10/4		Projection method
		ASSEMBLY KIT		Rev D
		Drawing number S1013358		

D	Change to Installation instruction	2012-03-22	se-henols
Rev	Type of revision	Date	Sign

We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©ROXTEC INTERNATIONAL AB