



5	1	INSTALLATION INSTR.	-		
4	1	ASSEMBLY GEL	-		
3	2	CM40 10-32	0+9,5-32,5		
2	2	CM 20W40	0+3,5-16		
1	1	COMSEAL 12 FRAME	POWDER COATED ALUMINUM		
ITE	QTY	Designation	Specification	Weight	
ROXTEC INTERNATIONAL AB		Designed by <b>se-henols</b>	Designed Date <b>2010-11-02</b>	General tolerance ISO 2768 M-10 EN 60 150-01	Detailed details EN ISO 10042-1 EN ISO 10042-2
SEJORAKE		Approved by <b>SEJORAKE</b>	Approved Date <b>2010-11-03</b>	General surface roughness, Ra 12,5	FatWeight
TEL: +46 455 396700 FAX: +46 455 82012		Format <b>A2</b>	Scale <b>1:-</b>	Title <b>COMSEAL 12/6 ASSEMBLY KIT</b>	Projection method 
Restricted due to Information Drawing		Drawing number <b>S1021977</b>		Rev <b>A</b>	

We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©ROXTEC INTERNATIONAL AB

A			
Rev	Type of revision	Date	Sign